

- Demolition: removal of any load-supporting structural member, or intentional burning of any facility.
- **Renovation**: altering a facility in any way, including stripping or removal of RACM.
- **RACM** (*Regulated asbestos-containing material*): ALL friable asbestos material, Category I non-friable ACM that is now friable, Category I non-friable ACM that will be or was subjected to sanding, grinding, cutting, or abrading, or Category II non-friable ACM that has a high probability of becoming or has become crumbled, pulverized, or reduced to powder by forces expected to act on material in course of demolition or renovation operations.
- **Category I nonfriable ACM**: asbestos-containing packings, gaskets, resilient floor covering, & asphalt roofing products containing more than 1% asbestos.
- <u>Category II nonfriable ACM</u>: material, excluding Category I nonfriable ACM, containing more than 1% asbestos that, when dry, cannot be crumbled, pulverized, or reduced to powder by hand pressure.
 NOTES:
- Prior to demolition or renovation, a <u>thorough inspection</u> must be conducted at facility CFR 61.145. Written asbestos notification certifying to the presence of ACM is required even if regulated ACM is not or may not be present Part 20.11.20.22 NMAC
- Owner/operator is responsible for ensuring ACM does not become RACM, unless it is accounted for in NESHAP & fees are paid (if applicable).
- These rules are not all inclusive refer to 40 CFR Part 61.145, Part 20.11.20.22 NMAC or the City's website, <u>http://www.cabq.gov/airquality/air-quality-permits/asbestos-program</u>, for additional information.