# FIRE CHIEF

Paul Dow 11500 Sunset Gardens Rd SW Albuquerque, NM 87121



# FIRE MARSHAL

Gene Gallegos 724 Silver SW Albuquerque, NM 87102

# **AUTOMATIC SPRINKLER SYSTEM CHECKLIST**

| PROJECT INFORMATION |                                  |           |             |  |  |  |
|---------------------|----------------------------------|-----------|-------------|--|--|--|
| Project Name        | Address and/or Legal Description | BP Number | Case Number |  |  |  |
|                     |                                  |           |             |  |  |  |

|     | PASS | ₽ | ¥<br>A   | REQUIREMENT  | CODE REF.          |
|-----|------|---|--|--|--------------------|
|     |      |   |  | NAME OF OWNER AND OCCUPANT.  | NFPA 13,<br>23.1.3 |
| 1   |      |   |  | LOCATION INCLUDING CEREET APPRECE  |                    |
| 2   |      |   |  | LOCATION, INCLUDING STREET ADDRESS.  | NFPA 13,<br>23.1.3 |
|     |      |   |  | POINT OF COMPASS.  | NFPA 13,           |
| 3   |      |   |  | TOWN OF COMPASS.   | 23.1.3             |
| 4   |      |   |  | FULL HEIGHT CROSS SECTION, OR SCHEMATIC DIAGRAM, INCLUDING STRUCTURAL MEMBER INFORMATION IF REQUIRED FOR CLARITY AND INCLUDING CEILING CONSTRUCTION AND METHOD OF PROTECTION FOR NONMETALLIC PIPING. | NFPA 13,<br>23.1.3 |
| 5   | П    | П | П  | LOCATION OF PARTITIONS.  | NFPA 13,<br>23.1.3 |
|     |      |   | <del>                                     </del> | LOCATION OF FIRE WALLS   | NFPA 13,           |
| 6   |      |   |  |  | 23.1.3             |
| 7   |      |   |  | OCCUPANCY CLASS OF EACH AREA OR ROOM.  | NFPA 13,           |
|     |      |   |  | LOCATION AND CITE OF CONCENTRACE CLOCKED ATTICC AND DATURGONG  | 23.1.3             |
|     |      |   |  | LOCATION AND SIZE OF CONCEALED SPACES, CLOSETS, ATTICS, AND BATHROOMS.   | NFPA 13,<br>23.1.3 |
| 8   |      |   |  | ANY SMALL ENCLOSURES IN WHICH NO SPRINKLERS ARE TO BE INSTALLED.   | NFPA 13,           |
| 9   |      |   |  | ANT SWIALL ENCLOSORES IN WHICH NO SPRINKLERS ARE TO BE INSTALLED.  | 23.1.3             |
| 40  |      |   |  | SIZE OF CITY MAIN IN STREET AND WHETHER DEAD END OR CIRCULATING; AND CITY MAIN TEST RESULTS AND  | NFPA 13,           |
| 10  |      |   |  | SYSTEM ELEVATION RELATIVE TO TEST HYDRANT.   | 23.1.3             |
| 11  | П    |   |  | OTHER SOURCES OF WATER SYPPLY, WITH PRESSURE OR ELEVATION.   | NFPA 13,           |
| 11  |      | Ш |  | MAKE TYPE MODEL AND NOMINAL K FACTOR OF CRRIMINIFES INCLUDING CRRIMINIFES INCLUDING  | 23.1.3<br>NFPA 13, |
| 12  |      |   |  | MAKE, TYPE, MODEL, AND NOMINAL K-FACTOR OF SPRINKLERS INCLUDING SPRINKLER IDENTIFICATION NUMBER.   | 23.1.3             |
|     |      |   |  | TEMPERATURE RATING AND LOCATION OF HIGH-TEMPERATURE SPRINKLERS.  | NFPA 13,           |
| 13  |      |   |  |  | 23.1.3             |
| 14  |      |   |  | TOTAL AREA PROTECTED BY EACH SYSTEM ON EACH FLOOR.   | NFPA 13,           |
| 14  |      |   |  | AN INADED OF CODIANY FOR ON FACULDICED DED FLOOD   | 23.1.3             |
| 15  |      |   |  | NUMBER OF SPRINKLERS ON EACH RISER PER FLOOR.  | NFPA 13,<br>23.1.3 |
|     |      |   |  | TOTAL NUMBER OF SPRINKLERS ON EACH DRY PIPE SYSTEM, PRE-ACTION SYSTEM, OR ACTION SYSTEM,   | NFPA 13,           |
| 16  |      |   |  | COMBINED DRY PIPE-PREACTION SYSTEM, OR DELUGE SYSTEM.  | 23.1.3             |
| 17  |      |   |  | APPROXIMATE CAPACITY IN GALLONS OF EACH DRY PIPE SYSTEM.   | NFPA 13,           |
| 1/  |      |   |  | DIDE TYPE AND COUEDING OF WALL THICKNIESS  | 23.1.3             |
| 18  |      |   |  | PIPE TYPE AND SCHEDULE OF WALL THICKNESS.  | NFPA 13,<br>23.1.3 |
| 4.0 |      |   |  | NOMINAL PIPE SIZE AND CUTTING LENGTHS OF PIPE (OR CENTER TO CENTER DIMENSIONS). WHERE TYPICAL  | NFPA 13,           |
| 19  |      |   |  | BRANCH LINES PREVAIL, IT SHALL BE NECESSARY TO SIZE ONLY ONE TYPICAL LINE.   | 23.1.3             |
| 20  | П    |   |  | LOCATION AND SIZE OF RISER NIPPLES.  | NFPA 13,           |
| 20  |      |   |  | TYPE OF FITTING AND IGNITE AND LOCATION OF ALL WEI DE AND DENDE. THE CONTRACTOR SHALL SPECIFY OF   | 23.1.3             |
| 21  |      |   |  | TYPE OF FITTING AND JOINTS AND LOCATION OF ALL WELDS AND BENDS. THE CONTRACTOR SHALL SPECIFY ON DRAWING ANY SECTIONS TO BE SHOP WELDED AND THE TYPE OF FITTINGS OR FORMATIONS TO BE USED.            | NFPA 13,<br>23.1.3 |
|     |      |   |  | TYPE AND LOCATIONS OF HANGERS, SLEEVES, BRACES, AND METHODS OF SECURING SPRINKLERS WHEN  | NFPA 13,           |
| 22  |      |   |  | APPLICABLE.  | 23.1.3             |

Fire Marshal's Office Plans Check Division

# FIRE CHIEF

Paul Dow 11500 Sunset Gardens Rd SW Albuquerque, NM 87121



# FIRE MARSHAL

Gene Gallegos 724 Silver SW Albuquerque, NM 87102

# **AUTOMATIC SPRINKLER SYSTEM CHECKLIST**

|    | PASS | Æ | N/A | REQUIREMENT   | CODE REF.          |
|----|------|---|-----|---|--------------------|
| 23 |      |   |     | ALL CONTROL VALVES, CHECK VALVES, DRAIN PIPES, AND TEST CONNECTIONS.                                | NFPA 13,           |
| 25 |      |   |     |   | 23.1.3             |
| 24 | П    |   |     | MAKE, TYPE, MODEL, AND SIZE OF ALARM OR DRY PIPE VALVE.   | NFPA 13,           |
|    |      |   |     | MAKEX TYPE, MODEL, AND SIZE OF PREACTION OR DELUGE VALVE.   | 23.1.3<br>NFPA 13, |
| 25 |      |   |     | WAREX TYPE, WODEL, AND SIZE OF PREACTION OR DELOGE VALVE.   | 23.1.3             |
|    |      |   |     | KIND AND LOCATION OF ALARM BELLS.   | NFPA 13,           |
| 26 |      |   |     |   | 23.1.3             |
| 27 |      |   |     | SIZE AND LOCATION OF STANDPIPE RISERS, HOSE OUTLETS, HAND HOSE, MONITOR NOZZLES, AND RELATED        | NFPA 13,           |
| 27 |      |   |     | EQUIPMENT.  | 23.1.3             |
| 20 |      |   |     | PRIVATE FIRE SERVICE MAIN SIZE, LENGTHS, LOCATIONS, WEIGHTS, MATERIALS, POINT OF CONNECTION TO CITY | NFPA 13,           |
| 28 |      |   |     | MAIN; THE SIZE, TYPES, AND LOCATIONS OF VALVES, VALVE INDICATORS, REGULATORRS, METERS, AND VALVE    | 23.1.3             |
|    |      |   |     | PITS; AND THE DEPTH THAT THE TOP OF THE PIPE IS LAID BELOW GRADE.                                   |                    |
| 20 |      |   |     | PIPING PROVISIONS FOR FLUSHING.   | NFPA 13,           |
| 29 |      |   |     |   | 23.1.3             |
| 30 |      |   |     | WHERE THE EQUIPMENT IS TO BE INSTALLED AS AN ADDITION TO AN EXISTING SYSTEM, ENOUGH OF THE          | NFPA 13,           |
| JU | Ш    | Ш | Ш   | EXISTING SYSTEM INDICATED ON THE PLANS TO MAKE ALL CONDITIONS CLEAR.                                | 23.1.3             |
| 31 | П    |   |     | FOR HYDRAULICALLY DESIGNED SYSTEMS, THE INFORMATION ON THE HYDRAULIC DATA NAMEPLATE.                | NFPA 13,           |
| J1 | -    |   | Ш   | A COLADULA DEDDECENTATION OF THE COLUE HOED ON ALL DIANG  | 23.1.3             |
| 32 | П    |   |     | A GRAPHIC REPRESENTATION OF THE SCALE USED ON ALL PLANS.  | NFPA 13,<br>23.1.3 |
|    |      |   |     | NAME AND ADDRESS OF CONTRACTOR.   | NFPA 13.           |
| 33 |      |   |     | NAINE AND ADDRESS OF CONTRACTOR.  | 23.1.3             |
|    |      |   |     | HYDRAULIC REFERENCE POINTS SHOWN ON THE PLAN THAT CORRESPOND WITH CAMPARABLE REFERENCE              | NFPA 13,           |
| 34 |      |   |     | POINTS ON THE HYDRAULIC CALCULATION SHEETS.   | 23.1.3             |
| 2- |      |   |     | THE MINIMUM RATE OF WATER APPLICATION (DENSITY OF FLOW OR DISACHARGE PRESSURE), THE DESIGN AREA     | NFPA 13,           |
| 35 |      |   |     | OF WATER APPLICATION, IN-RACK SPRINKLER DEMAND, AND THE WATER REQUIRED FOR HOSE STREAMS BOTH        | 23.1.3             |
|    |      |   |     | INSISE AND OUTSIDE.   |                    |
| 36 |      |   |     | THE TOTAL QUANTITY OF WATER AND THE PRESSURE REQUIRED NOTED AT A COMMON REFERENCE POINT FOR         | NFPA 13,<br>23.1.3 |
|    |      |   |     | EACH SYSTEM.  |                    |
| 37 |      |   |     | RELATIVE ELEVATIONS OF SPRINKLER, JUNCTION POINTS, AND SUPPLY OR REFERENCE POINTS.                  | NFPA 13,<br>23.1.3 |
| 38 |      |   |     | IF ROOM DESIGN METHOD IS USED, ALL UNPROTECTED WALL OPENINGS THOUGHOUT THE FLOOR PROTECTED.         | NFPA 13.           |
| 50 |      |   |     | II ROOM DESIGN METHOD IS OSED, ALE ON ROTECTED WALL OF LININGS THOUGHOUT THE TEOUR PROTECTED.       | 23.1.3             |
| 39 |      |   |     | CALCULATION OF LOADS FOR SIZING AND DETAILS OF SWAY BRACING.  | NFPA 13,           |
|    |      |   |     |   | 23.1.3             |
| 40 |      |   |     | THE SETTING FOR PRESSURE-REDUCING VALVES.   | NFPA 13,           |
|    |      |   |     |   | 23.1.3             |
| 41 |      |   |     | INFORMATION ABOUT BACKFLOW PREVENTERS (MANUFACTURER, SIZE, TYPE).                                   | NFPA 13,           |
| 42 |      |   |     | INFORMATION ADOLIT ANTIFRETTE COLUTION LICED /TVPE AND ARACUNITY                                    | 23.1.3<br>NFPA 13, |
| 42 |      |   |     | INFORMATION ABOUT ANTIFREEZE SOLUTION USED (TYPE AND AMOUNT).                                       | 23.1.3             |
| 43 |      |   |     | SIZE AND LOCATION OF HYDRANTS, SHOWING SIZE AND NUMBER OF OUTLETS AND IF OUTLETS ARE TO BE          | NFPA 13,           |
| 73 |      |   |     | QUIPPED WITH INDEPENDENT GATE VALVES. WHETER HOSE HOUSES AND EQUIPMENT ARE TO BE PROVIDED,          | 23.1.3             |
|    |      |   |     | AND BY WHOM, SHALL BE INDICATED. STATIC AND RESIDUAL HYDRANTS THAT WERE USED IN FLOW TESTS          |                    |
|    |      |   |     | SHALL BE SHOWN  |                    |
| 44 |      |   |     | SIZE, LOCATION, AND PIPING ARRANGEMENT OF FIRE DEPARTMENT CONNECTIONS.                              | NFPA 13,           |
|    |      |   |     | Size, 200 mon, and in morament of the Definition Connections.                                       | 23.1.3             |
| 45 |      |   |     | CEILING/ROOF HEIGHTS AND SLOPES NOT SHOWN IN THE FULL HEIGHT CROSS SECTION.                         | NFPA 13,           |
|    |      |   |     | ·   | 23.1.3             |
| 46 |      |   |     | EDITION YEAR OF NFPA 13 THAT THE SPRINKLER SYSTEM IS DESIGNED TO.                                   | NFPA 13,           |
|    |      |   |     |   | 23.1.3             |

# FIRE CHIEF

Paul Dow 11500 Sunset Gardens Rd SW Albuquerque, NM 87121



FIRE MARSHAL Gene Gallegos 724 Silver SW

Albuquerque, NM 87102

# **AUTOMATIC SPRINKLER SYSTEM CHECKLIST**